



ARISA-TACK

Hot Melt Adhesives for Wood working

Arisa Baspar Pars

Product Description

Arisa Baspar uses the finest raw materials and advanced manufacturing processes to produce unique, high-performance hot melt woodworking adhesive.

Features

- tested on all major woodworking machines
- high tackiness
- resistant to external factors
- non-toxic
- unfilled adhesives, providing a low flow rate
- low level of thread formation, not lubricated
- long open time combined with high thermal stability

Product	Viscosity (cp) at 180°C	Softening point (°C)	Open time	color	Application	operation temp(°C)
ARISATAACK 5401	20000-30000	120-130	Medium	Yellowish pellet	Bonds well to wood ,Particleboard ,MDF ,fabric furniture Foam lamination Wood working Pre coating Profile Wrapping Edge banding Soft forming Foam Bonding V-Grooving, Top Laminating and General Assembly Bonds well to wood ,Particleboard ,MDF ,fabric furniture Foam lamination Wood working Pre coating Profile Wrapping Edge banding Soft forming Foam Bonding V-Grooving, Top Laminating and General Assembly	190-210
ARISATAACK 5402	30000-40000	120-130	Medium	Yellowish pellet	Bonds well to wood ,Particleboard ,MDF ,fabric furniture Foam lamination Wood working Pre coating Profile Wrapping Edge banding Soft forming Foam Bonding V-Grooving, Top Laminating and General Assembly Pocket coil assembly Upholstery layer /pillow top attachment Mattress ticking Foam lamination	190-210
ARISATAACK 5203	3000-4000	120-130	Medium	White pellet	Bonds well to wood ,Particleboard ,MDF ,fabric furniture Foam lamination Wood working Pre coating Profile Wrapping Edge banding Soft forming Foam Bonding V-Grooving, Top Laminating and General Assembly Pocket coil assembly Upholstery layer /pillow top attachment Mattress ticking Foam lamination	160-190